

UNI-T®

UT340 SERIES Coating Thickness Gauges

UT342



EN61326-1

SPECIFICATIONS



Specifications	Range	Best Accuracy
Model		UT342
Iron Matrix Measurement	0µm~55µm	±3dgt
	56µm~1000µm	±(3.0%+1dgt)
Aluminum Matrix Measurement	0µm~55µm	±3dgt
	56µm~1000µm	±(3.0%+1dgt)
Resolution	1µm	√
Features		
Maximum Display		9999
Auto Power Off		√
Low Battery Indication		√
MAX/MIN		√
Data Storage		2000
LCD Backlight		√
Measurement Mode	Continuous or Single Measurement	√
Key Mis-press Buzzer		√



■ UT342

GENERAL CHARACTERISTICS

Power	9V Battery(6LF22)
LCD Size	22mm × 22mm
Product Color	Red and Grey
Product Net Weight	144.2 g
Product Size	153mm × 110mm × 40mm
Standard Accessories	UT342-Battery,Standard Membrane Slice, Iron Matrix Slice, Aluminum Matrix Slice,Carrying Bag
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	620mm × 400mm × 245mm (0.061 CBM Per Standard Carton)
Standard Carton Gross Weight	13 kg

Uni-Trend Your Testing Specialist!