




Models	UT681L	UT681C	UT681HDMI
Page	159	159	159
			
To test for: RJ45/RJ11	●		
To test for: RJ45/RJ11/BNC		●	
To test for: HDMI/MINI-HDMI			●
Fast test mode	LED1~LED8, LED_G	LED1~LED8, LED_G	
Slow test mode	LED1~LED8, LED_G	LED1~LED8, LED_G	
Scan test mode			LED1~LED19, LED_S
Full display test mode			LED1~LED19, LED_S
To test for the case of short circuit, crossover, open circuit, etc.	●	●	●
Ethernet cable: shielded/unshielded test	●	●	●
Manual shutdown function	●	●	●
Auto shutdown function	●	●	●
Single key operation	●	●	●
Power supply: 9V battery	●	●	●
Low battery detection	●	●	●
Certificates	CE/UKCA	CE/UKCA	CE/UKCA



UT681L

UT681C

UT681HDMI

Specifications	Description	UT681L	UT681C	UT681HDMI
Certificates	CE, UKCA			
To test for: RJ45/RJ11		√		
To test for: RJ45/RJ11/BNC	Need to use RJ45 to BNC adaptor		√	
To test for: HDMI/Mini-HDMI				√
Fast test mode	LED1~LED8, LED_G	√	√	
Slow test mode	LED1~LED8, LED_G	√	√	
Scan test mode	LED1~LED19, LED_S			√
Full display test mode	LED1~LED19, LED_S			√
To test for the case of short circuit, crossover, open circuit, etc.		√	√	√
Ethernet cable: shielded/ unshielded test		√	√	√
Manual shutdown function		√	√	√
Auto shutdown function	No operation within 10 minutes	√	√	√
Single key operation		√	√	√
Power supply: 9V battery		√	√	√
Low battery detection	Less than 7.2V	√	√	√
Working temperature: 0°C~40°C		√	√	√
Storage temperature: -10°C~50°C		√	√	√
Working humidity: 20~80%RH		√	√	√
Storage humidity: 10~90%RH		√	√	√
Altitude: ≤2000 meters		√	√	√
Safety standard	EN61326-1: 2013; EN61326-2-2: 2013	√	√	√

Characteristics	
Standard accessories	9V battery, BNC to RJ45 adaptor (UT681C), English manual
Product size	Transmitter: 102 x 62 x 28mm; receiver: 102 x 37 x 28mm
Product net weight	Transmitter: 87g; receiver: 51g
Standard individual packing	Gift box
Standard quantity per carton	40pcs
Standard carton measurement	455 x 410 x 225mm
Standard carton gross weight	UT681L: 6.4kg; UT681C: 8.7kg; UT681HDMI: 9.5kg