







Models	LM555LD	LM570LD-II	LM573LD-II	LM575LD	LM576LD	LM585LD
Page	139	138	138	138	138	138
						
Laser type	green LD	green LD	green LD	green LD	Osram green LD	Osram green LD
Laser wavelength	520nm	520nm	520nm	520nm	520nm	520nm
Laser class	Class II	Class II	Class II	Class II	Class II	Class II
Laser lines	1H 4V 1D	1V1H	3D 12 lines	3D 12 lines	3D 16 lines	8 lines
Laser accuracy	±2mm/10m	<±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m
Wall mount			●		●	
Bracket included		●				●
Expanded angle	V≥110°, H≥130°	V≥120°, H≥120°	360°	360°	360°	360°
Self-leveling time	≤3s	≤3s	≤3s	≤3s	≤3s	≤3s
Self-leveling range	3° (±0.5°)	3°±1°	3°±1°	3°±1°	±3°	±3°
Self-leveling alarm	●	●	●	●	●	●
Outdoor pulse mode	●		●	●	●	●
Graduated collar	●					
Remote control			●	●	●	●
Operating distance	25m (point) /20m (line)	10m	40m	40m	30m	30m
Size of screw hole	5/8"	1/4"	1/4"	1/4"	1/4"	1/4"
Battery capacity	3.7V Li-ion battery 4000mAh	2x1.5V LR6 AA	3.7V Li-ion battery 5200mAh /Type-C DC-in port	3.7V Li-ion battery 5200mAh /Type-C DC-in port	3.7V Li-ion battery 5200mAh /Type-C DC-in port	3.7V Li-ion battery 5200mAh /Type-C DC-in port
Working hours	>5h	4h	>6h	>6h	>4h	>4h
IP rating	IP54					
Certificates		CE/UKCA		CE/UKCA		

These laser levelers are equipped with green LD laser, suitable for large or bright work places. Its applications include: horizontal, vertical, cross line projection for decoration, building construction, home decoration, renovation, furniture installation, flooring, and project layout.



**LM312 wall mount**  
LM312 is suitable for  
LM573LD-II/575LD/576LD only.



LM576LD

Specifications	LM570LD-II	LM573LD-II	LM575LD	LM576LD	LM585LD
<b>Certificates (LM570LD-II/575LD only)</b>	CE, UKCA				
Laser type	Green LD	Green LD	Green LD	Osram green LD	Osram green LD
Laser lines	2 lines	3D 12 lines	3D 12 lines	3D 16 lines	8 lines
Operating distance	10m	40m	40m	30m	30m
Laser accuracy	±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m
Outdoor pulse mode		√	√	√	√
Remote control		√	√	√	√
Self-leveling range	3°±1°	±3°	±3°	±3°	±3°
Self-leveling time	3s	<3s	<3s	<3s	<3s
Working hours	4h	>6h	>6h	>4h	>4h
Laser wavelength	520nm				
Laser class	2				

#### Features

Osram LD green laser(LM576/585LD)	Self-leveling mode & manual mode
Outdoor pulse mode	5200mAh Li-ion battery
Type-C DC-in port	includes wall mount (LM573LD-II/575LD/576LD)

#### Characteristics

Standard accessories	USB cable, adapter, English manual
Power	LM570LD-II: 1.5V battery x 2 (LR6); LM573LD-II/LM575LD/LM576LD/LM585LD: 3.7V Li-ion battery 5200mAh
Product size	LM570LD-II: 85.5 x 62 x 90.3mm; LM573LD-II: 119 x 89 x 138mm; LM575LD/LM576LD: 138 x 89 x 147mm; LM585LD: 138 x 89 x 136mm
Product net weight	LM570LD-II: 240g; LM573LD-II/LM575LD: 694g; LM576LD: 653g; LM585LD: 591g
Standard individual packing	Gift box, tool box
Standard quantity per carton	LM570LD-II: 20pcs; LM573LD-II/LM575LD/LM576LD/LM585LD: 4pcs
Standard carton measurement	LM570LD-II: 420mm x 320mm x 350mm; LM573LD-II/LM575LD/LM576LD/LM585LD: 620mm x 355mm x 325mm
Standard carton gross weight	LM570LD-II: 10.71kg; LM573LD-II/LM575LD/LM576LD: 10.63kg; LM585LD: 10.22kg