

Models	UT123	UT123T	UT123D	UT125C	UT133A	UT133B	UT60S	UT60EU	UT60BT
Page	067	067	066	068	069	069	052	053	053
DC voltage (V)	600V	600V	600V	600V	600V	600V	1000V	1000V	1000V
AC voltage (V)	600V	600V	600V	600V	600V	600V	1000V	1000V	1000V
DC current (A)			10A	400mA	10A	10A	10A	10A	10A
AC current (A)			10A	400mA	10A		10A	10A	10A
Resistance (Ω)	20M Ω	20M Ω	40M Ω	40M Ω	60M Ω	60M Ω	100M Ω	100M Ω	100M Ω
Capacitance (F)			4000 μ F	100 μ F	10mF	10mF	100mF	10mF	10mF
Frequency (Hz)				60kHz	1MHz		10MHz	10MHz	10MHz
Temperature ($^{\circ}$ C)	-40 $^{\circ}$ C~300 $^{\circ}$ C	-40 $^{\circ}$ C~300 $^{\circ}$ C			-40 $^{\circ}$ C~1000 $^{\circ}$ C		-40 $^{\circ}$ C~1000 $^{\circ}$ C	-40 $^{\circ}$ C~1000 $^{\circ}$ C	-40 $^{\circ}$ C~1000 $^{\circ}$ C
Features									
Display count	4000	4000	4000	4000	6000	6000	9999	9999	9999
Diode/continuity	Continuity	Continuity	•	•	•	•	•	•	•
Low battery indication	•	•	•	•	•	•	•	•	•
Data hold	•	•	•	•	•	•	•	•	•
Auto power off	•	•	•	•	•	•	•	•	•
LCD backlight				•	•	•	•	•	•
Duty cycle				•			•	•	•
Relative mode					•	•	•	•	•
NCV	•	•	•	•	•	•	•	•	•
Auto range	•	•	•	•	•		•	•	•
True RMS			•				•	•	•
Bluetooth/APP									•
Safety Features									
Drop test	1m	1m	1m	1m	1m	1m	1m	1m	1m
Safety rating	CAT III 600V						CAT II 1000V/CAT III 600V		
Certificates		CE/UKCA /cETLus	CE/UKCA	CE/UKCA /cETLus	CE/UKCA /cETLus	CE/UKCA /cETLus	CE/UKCA/cETLus		



UT60S

Specification	Range	Accuracy
Certificates	CE, UKCA, cETLus	
DC voltage (V)	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	±(0.5%+3)
AC voltage (V)	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	±(0.8%+3)
DC current (A)	999.9μA/999.9mA/9.999A	±(0.8%+3)
AC current (A)	999.9μA/999.9mA/9.999A	±(1.0%+3)
Resistance (Ω)	99.99Ω/999.9Ω/9.999kΩ/99.99kΩ/999.9kΩ/9.999MΩ/99.99MΩ	±(0.8%+2)
Capacitance (F)	9.999nF/99.99nF/999.9nF/9.999μF/99.99μF/999.9μF/9.999mF/99.9mF	±(4%+5)
Frequency	9.999Hz~9.999MHz	±(0.1%+5)
Duty cycle	0.1~99.9%	±(3%+5)
Temperature	-40°C~1000°C/-40°F~1832°F	±4°C/±5°F

Features	
Display count	9999
Auto range	√
NCV	√
Diode/REL	√
Continuity test	√
Acousto-optic indication(NCV/continuity/battery power)	√
Low battery indication	≤3.6V
Data hold	√
Auto power off	15Min
Operation temperature	0°C~40°C
Safety	CATII 1000V/CATIII 600V

General Characteristics	
Battery	1.5VAAA x3
Product color	Red and Gray
Product net weight	290g
Product size	169 x 81 x 46mm
Standard individual packing	Gift Box, Manual, Thermocouple
Standard quantity per carton	20pcs
Standard carton size	420 x 320 x 300mm