

## .093" (2,36mm) Diameter Terminals

### 8891-N Series










inches  
mm

- Integrally molded polarization
- 94V-2 and 94V-0 nylon
- Accepts Alex .093" (2.36mm) crimp type
- 1, 2, 3, 4, 6, 9, 12, 15 circuit versions

- UL File No.: E114003
- Positive locking
- Integrally molded mounting ears available on plug only
- .16" (4mm) over surface and .12" (3mm) through air spacing between terminals

- CSA File No.: LR 86545
- Standard color natural. Can be color coded in black, brown, green, gray, orange, amber, red or yellow
- .264" (6.71mm) grid pattern

Circuits	Max. Rated		Dimensional Information	
	Amps	Voltage	Plug	Receptacle
1	12A	600V	<p>8891-01F 8891-01F1 (W/O Mtg. Ears)</p>	<p>8891-01M1 (W/O Mtg. Ears)</p>
2	12A	600V	<p>8891-02F 8891-02F1 (W/O Mtg. Ears)</p>	<p>8891-02M1 (W/O Mtg. Ears)</p>
3	11A	600V	<p>8891-03F 8891-03F1 (W/O Mtg. Ears)</p>	<p>8891-03M1 (W/O Mtg. Ears)</p>

Circuits	Max. Rated		Dimensional Information	
	Amps	Voltage	Plug	Receptacle
4	9A	600V	8891-04F 8891-04FI (W/O Mtg. Ears) 	8891-04MI (W/O Mtg. Ears) 
6	9A	600V	8891-06F 8891-06FI (W/O Mtg. Ears) 	8891-06MI (W/O Mtg. Ears) 
9	8A	600V	8891-09F 8891-09FI (W/O Mtg. Ears) 	8891-09MI (W/O Mtg. Ears) 
12	7A	600V	8891-12F 8891-12FI (W/O Mtg. Ears) 	8891-12MI (W/O Mtg. Ears) 
15	6A	600V	8891-15F 8891-15FI (W/O Mtg. Ears) 	8891-15MI (W/O Mtg. Ears) 